

8.5mm Subminiature Low breaking Capacity, Fast Blow Fuse-Round type

Rated Current (A)	*Cooper Bussman	Littelfuse	Schurter	Protectron
0.05	-	3700050	0034.6000	PRFLT 0.05A
0.063	-	3700063	0034.6001	PRFLT 0.063A
0.08	-	3700080	0034.6002	PRFLT 0.08A
0.1	-	3700100	0034.6003	PRFLT 0.1A
0.125	-	3700125	0034.6004	PRFLT 0.125A
0.16	-	3700160	0034.6005	PRFLT 0.16A
0.2	-	3700200	0034.6006	PRFLT 0.2A
0.25	-	3700250	0034.6007	PRFLT 0.25A
0.315	-	3700315	0034.6008	PRFLT 0.315A
0.4	-	3700400	0034.6009	PRFLT 0.4A
0.5	-	3700500	0034.6010	PRFLT 0.5A
0.63	-	3700630	0034.6011	PRFLT 0.63A
0.8	SR-5F-800mA	3700800	0034.6012	PRFLT 0.8A
1	SR-5F-1A	3701100	0034.6013	PRFLT 1A
1.25	SR-5F-1.25A	3701125	0034.6014	PRFLT 1.25A
1.6	SR-5F-1.6A	3701160	0034.6015	PRFLT 1.6A
2	SR-5F-2A	3701200	0034.6016	PRFLT 2A
2.5	SR-5F-2.5A	3701250	0034.6017	PRFLT 2.5A
3.15	SR-5F-3.15A	3701315	0034.6018	PRFLT 3.15A
4	SR-5F-4A	3701400	0034.6019	PRFLT 4A
5	SR-5F-5A	3701500	0034.6020	PRFLT 5A
6.3	SR-5F-6.3A	3701630	-	PRFLT 6.3A

* As Per UL Standard UL248-14

8.5mm Subminiature Low breaking Capacity, Fast Blow Fuse-Rectangular type

Rated Current (A)	*Cooper Bussman	*LittelFuse	Schurter	Protectron
0.05	-	3950050	-	PRFLT 0.05A-R
0.063	-	3950063	-	PRFLT 0.063A-R
0.08	-	3950080	-	PRFLT 0.08A-R
0.1	-	3950100	-	PRFLT 0.1A-R
0.125	-	3950125	-	PRFLT 0.125A-R
0.16	-	3950160	7100.1057	PRFLT 0.16A-R
0.2	-	3950200	7100.1058	PRFLT 0.2A-R
0.25	-	3950250	7100.1059	PRFLT 0.25A-R
0.315	-	3950315	7100.1060	PRFLT 0.315A-R
0.4	-	3950400	7100.1061	PRFLT 0.4A-R
0.5	-	3950500	7100.1062	PRFLT 0.5A-R
0.63	-	3950630	7100.1063	PRFLT 0.63A-R
0.8	SS-5F-800mA	3950800	7100.1064	PRFLT 0.8A-R
1	SS-5F-1A	3951100	7100.1065	PRFLT 1A-R
1.25	SS-5F-1.25A	3951125	7100.1066	PRFLT 1.25A-R
1.6	SS-5F-1.6A	3951160	7100.1067	PRFLT 1.6A-R
2	SS-5F-2A	3951200	7100.1068	PRFLT 2A-R
2.5	SS-5F-2.5A	3951250	7100.1069	PRFLT 2.5A-R
3.15	SS-5F-3.15A	3951315	7100.1070	PRFLT 3.15A-R
4	SS-5F-4A	3951400	7100.1071	PRFLT 4A-R
5	SS-5F-5A	3951500	7100.1072	PRFLT 5A-R
6.3	SS-5F-6.3A	3951630	7100.1073	PRFLT 6.3A-R

* As Per UL Standard UL248-14

**Protectron Electromech Pvt Ltd, No.44, 29th Cross, 7th Main, BSK Indl. Layout,
BSK 2nd stage, Bangalore-560 070, Tel.: +91 80 26716001-05
email: protectron@protectron.in
website: www.protectron.in**

8.5mm Subminiature Low breaking Capacity, Slow Blow Fuse-Round type

Rated Current (A)	Cooper Bussmann	Littelfuse	Schurter	Protectron
0.05	-	-	0034.6602	PRTL 0.05A
0.063	-	-	0034.6603	PRTL 0.063A
0.08	-	-	0034.6604	PRTL 0.08A
0.1	SR-5-100mA	-	0034.6605	PRTL 0.1A
0.125	SR-5-125mA	-	0034.6606	PRTL 0.125A
0.16	SR-5-160mA	-	0034.6607	PRTL 0.16A
0.2	SR-5-200mA	-	0034.6608	PRTL 0.2A
0.25	SR-5-250mA	-	0034.6609	PRTL 0.25A
0.315	SR-5-315mA	-	0034.6610	PRTL 0.315A
0.4	SR-5-400mA	-	0034.6611	PRTL 0.4A
0.5	SR-5-500mA	-	0034.6612	PRTL 0.5A
0.63	SR-5-630mA	-	0034.6613	PRTL 0.63A
0.8	SR-5-800mA	-	0034.6614	PRTL 0.8A
1	SR-5-1A	3821100	0034.6615	PRTL 1A
1.25	SR-5-1.25A	3821125	0034.6616	PRTL 1.25A
1.6	SR-5-1.6A	3821160	0034.6617	PRTL 1.6A
2	SR-5-2A	3821200	0034.6618	PRTL 2A
2.5	SR-5-2.5A	3821250	0034.6619	PRTL 2.5A
3.15	SR-5-3.15A	3821315	0034.6620	PRTL 3.15A
4	SR-5-4A	3821400	0034.6621	PRTL 4A
5	SR-5-5A	3821500	0034.6622	PRTL 5A
6.3	SR-5-6.3A	3821630	0034.6623	PRTL 6.3A

8.5mm Subminiature Low breaking Capacity, Slow Blow Fuse-Rectangular type

Rated Current (A)	Cooper Bussmann	Littelfuse	Protectron
0.25	-	-	PRTLTL 0.25A-R
0.315	-	-	PRTLTL 0.315A-R
0.4	SS-5-400mA	-	PRTLTL 0.4A-R
0.5	SS-5-500mA	-	PRTLTL 0.5A-R
0.63	SS-5-630mA	-	PRTLTL 0.63A-R
0.8	SS-5-800mA	3920800	PRTLTL 0.8A-R
1	SS-5-1A	3921100	PRTLTL 1A-R
1.25	SS-5-1.25A	3921123	PRTLTL 1.25A-R
1.6	SS-5-1.6A	3921160	PRTLTL 1.6A-R
2	SS-5-2A	3921200	PRTLTL 2A-R
2.5	SS-5-2.5A	3921250	PRTLTL 2.5A-R
3.15	SS-5-3.15A	3921315	PRTLTL 3.15A-R
4	SS-5-4A	3921400	PRTLTL 4A-R
5	SS-5-5A	3921500	PRTLTL 5A-R
6	SS-5-6.3A	3921630	PRTLTL 6.3A-R