




PROTECTRON ELECTROMECH (P) LTD

**DESCRIPTION : FEMALE HEADER 2.54mm PITCH, DUAL ROW
RIGHT ANGLE, PROFILE: 5.7mm**

PART NO:P9404AXX-XX
1st XX=NO. OF CONTACTS(4-80)
2nd XX=TYPE OF PLATING

RoHS



PHYSICAL

INSULATION

MATERIAL : GLASS FILLED POLYESTER
FLAMMABILITY : UL94V-0
COLOR : BLACK

CONTACT

MATERIAL : COPPER ALLOY
SOLDER TAILS : REFER TABLE
PACKAGING TYPE : TUBE/TRAY

ELECTRICAL

CURRENT RATING : 3A
INSULATION RESISTANCE : 5000M OHMS MIN
DIELECTRIC WITHSTANDING : 500V AC/MIN
CONTACT RESISTANCE : 20m OHMS MAX

MECHANICAL DATA

INSERTION FORCE : 200g max.
EXTRACTION FORCE : 20g min.
MECHANICAL LIFE : 100 CYCLES min.

ENVIRONMENTAL DATA


TEMPERATURE RANGE : -40°C TO +105°C
PROCESS RATING : 180°C FOR 5SEC



PROTECTRON ELECTROMECH (P) LTD

DESCRIPTION : FEMALE HEADER 2.54mm PITCH, DUAL ROW
RIGHT ANGLE, PROFILE: 5.7mm

PART NO: P9404AXX-XX
1st XX=NO. OF CONTACTS(4-80)
2nd XX=TYPE OF PLATING



RECOMMENDED P.C.B. LAYOUT

A	ORIGINAL			SACHIN	30.07.2004		
REV.	DESCRIPTION			DRN. BY	DATE	CK'ED BY	APP'D BY
Projection: 		Scale: NTS	Sht. Size: A4	Gen. Tol.: ± 0.35 mm	ALL DIMENSIONS ARE IN MM. IF UNLESS OTHERWISE SPECIFIED.		



PROTECTRON ELECTROMECH (P) LTD

DESCRIPTION : FEMALE HEADER 2.54mm PITCH, DUAL ROW
RIGHT ANGLE, PROFILE: 5.7mm

PART NO: P9404AXX-XX

1st XX=NO. OF CONTACTS(4-80)
2nd XX=TYPE OF PLATING

ORDERING INFORMATION

P9404A-XX-XX

NO OF CONTACTS
(4-80)

TYPE OF PLATING

XX	PLATING
21	GOLD FLASH
22	0.75 μ GOLD
23	GOLD FLASH ON CONTACT SIDE & TIN ON SOLDER SIDE
24	5 μ TIN

MATES WITH

P9103,P9104
P9105,P9108

MOQ- ----

SPQ- ----