PROTECTRON ELECTROMECH (P) LTD

DESCRIPTION : FEMALE HEADER 2.0mm PITCH DOUBLE ROW, SMT, BOTTOM ENTRY

PART NO: P9415AXX-XX
1st XX=NO. OF CONTACTS
2nd XX=TYPE OF PLATING

RoHS



PHYSICAL

INSULATION	:	
MATERIAL	:	POLYESTER
FLAMMABILITY	:	UL94V-0
COLOR	:	BLACK
CONTACT	:	
MATERIAL	:	COPPER ALLOY
SOLDER TAILS	:	GOLD PLATED
PACKAGING TYPE	:	TUBE/TRAY

ELECTRICAL

CURRENT RATING	:	2A
INSULATION RESISTANCE	:	1000M OHMS MIN
DIELECTRIC WITHSTANDING	:	500V AC/MIN
CONTACT RESISTANCE	:	20m OHMS MAX
VOLTAGE RATING	:	250V AC

ENVIRONMENTAL DATA

TEMPERATURE RANGE	:	-40°C TO +105°C
PROCESS RATING	:	180°C FOR 5SEC

PROTECTRON ELECTROMECH (P) LTD

DESCRIPTION : FEMALE HEADER 2.0mm PITCH DOUBLE ROW, SMT, BOTTOM ENTRY

PART NO: P9415AXX-XX
1st XX=NO. OF CONTACTS
2nd XX=TYPE OF PLATING



REV.	DESCRIPTION	DRN. BY	DATE	CK'ED BY	APP'D BY
A	ORIGINAL	CHETAN	11.07.2011		

Projection:	Scale: NTS	Sht. Size: A4	Gen. Tol.: ±0.1mm ±1°	ALL DIMENSIONS ARE IN MM. IF UNLESS OTHERWISE SPECIFIED.

http://www.protectron.in
protectron@protectron.in

PROTECTRON ELECTROMECH (P) LTD

DESCRIPTION : FEMALE HEADER 2.0mm PITCH DOUBLE ROW, SMT, BOTTOM ENTRY

PART NO: P9415AXX-XX
1st XX=NO. OF CONTACTS
2nd XX=TYPE OF PLATING

ORDERING INFORMATION

P9415AXX-XX

NO OF CONTACTS (10-60)

XX	PLATING
21	GOLD FLASH
22	0.75μ GOLD
23	GOLD FLASH ON CONTACT SIDE & TIN ON SOLDER SIDE
24	5μ TIN

MATES WITH

P9113,P9114
P9115,P9118

MOQ- ----
SPQ- ----