



NOTE: M5 THREADED STUDS & HEX NUTS WITH LOCK WASHERS TO BE USED FOR FUSE HOLDING.
M4 STUDS TO BE USED FOR MOUNTING THE FUSE HOLDER.

PHYSICAL INSULATION	
MATERIAL	PA
FLAMMABILITY	UL94V-0
BOLTS, NUTS & WASHER	STAINLESS STEEL 304
PACKAGING TYPE	STANDARD PACKING

ELECTRICAL DATA	
MAX. VOLTAGE RATING	: 32V DC
MAX. FUSE RATING	: 200A
WIRE SIZE	: 25mm ²

MECHANICAL DATA	
TORQUE RATING	: 5Nm

ENVIRONMENTAL DATA	
TEMPERATURE RANGE	: -40°C TO +125°C

4	CONTACT (BOLT/NUT/WASHER)	STEEL 304
3	WINDOW COVER	PC UL94 V-0
2	COVER	PA UL94 V-0
1	BASE	PA UL94 V-0
SI NO.	DESCRIPTION	MATERIAL & FINISH

REV.	ZONE	DESCRIPTION	DRG REV BY	DATE	DOCUMENT CODE :	HEAT TREATMENT	ENG APP'D :	APP'D BY :	DATE :	ALL DIMENSIONS ARE IN MM. IF UNLESS OTHERWISE SPECIFIED.
A		ORIGINAL		13.09.2014	4D P803B 01	---			13.09.2014	This Document is the property of PROTECTRON ELECTROMECH (P) LTD. It shall not be reproduced or communicated to a third party without prior permission. DWG according to STD. Sheet: 1 OF 1
A1		ELECTRICAL & MECHANICAL DETAILS ADDED	AKSHAY	23.12.2019	SEE ABOVE TABLE					

PROTECTRON ELECTROMECH (P) LTD.
Bangalore, INDIA.

