




PROTECTRON®
ELECTROMECH (P) LTD

DESCRIPTION : WAFER 3.00mm PITCH MICROFIT, DOUBLE ROW,
R/A WITH PEGS

PART NO: P9066R20-1X-X
X=NO. OF WAYS(2-24)

RoHS



PHYSICAL DATA

INSULATION

MATERIAL : PBT 30% GF

FLAMMABILITY : UL94V-0

COLOR : BLACK COLOR

CONTACT

MATERIAL : COPPER ALLOY

FINISH : GOLD PLATED

PACKAGING TYPE : STANDARD

ELECTRICAL DATA

CURRENT RATING : 5A

INSULATION RESISTANCE : 1000M OHMS MIN

DIELECTRIC WITHSTANDING : 1500V AC/MIN

CONTACT RESISTANCE : 10m OHMS MAX

VOLTAGE RATING : 250V AC/DC

ENVIRONMENTAL DATA





TEMPERATURE RANGE : -25° TO +85° C



PROTECTRON[®]
ELECTROMECH (P) LTD

DESCRIPTION : WAFER 3.00mm PITCH MICROFIT, DOUBLE ROW,
R/A WITH PEGS

PART NO: P9066R20-1X-X
X=NO. OF WAYS(2-24)



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)

Projection:



Scale: NTS

Sht. Size: A4

Gen. Tol.: ±0.35mm

ALL DIMENSIONS ARE IN MM.
IF UNLESS OTHERWISE SPECIFIED.



PROTECTRON[®]
ELECTROMECH (P) LTD

DESCRIPTION :WAFER 3.00mm PITCH MICROFIT, DOUBLE ROW,
R/A WITH PEGS

PART NO: P9066R20-1X-X
X=NO. OF WAYS(2-24)

ORDERING INFORMATION

P9066R20-1X-X

TYPE OF PLATING

NO OF WAYS
(2-24)

PART NO (TIN PLATED)	PART NO (GOLD PLATED)	DIMENSIONS	
		A	B
P9066R20-19-2	P9066R20-12-2	--	6.65
P9066R20-19-4	P9066R20-12-4	3.00	9.65
P9066R20-19-6	P9066R20-12-6	6.00	12.65
P9066R20-19-8	P9066R20-12-8	9.00	15.65
P9066R20-19-A	P9066R20-12-A	12.00	18.65
P9066R20-19-C	P9066R20-12-C	15.00	21.65
P9066R20-19-E	P9066R20-12-E	18.00	24.65
P9066R20-19-G	P9066R20-12-G	21.00	27.65
P9066R20-19-I	P9066R20-12-I	24.00	30.65
P9066R20-19-K	P9066R20-12-K	27.00	33.65
P9066R20-19-M	P9066R20-12-M	30.00	36.65
P9066R20-19-O	P9066R20-12-O	33.00	39.65

MATES WITH

P9066H/ P9066T

Projection:



Scale: NTS

Sht. Size: A4

Gen. Tol.:±0.35mm

ALL DIMENSIONS ARE IN MM.
IF UNLESS OTHERWISE SPECIFIED.