



DESCRIPTION : IDC SOCKET 2.54mm PITCH DUAL ROW,
RoHS COMPLIANT

PART NO: P9403IDS-XX-2XX-XX
XX = No.OF CONTACTS
(06-26,30,34,36,40,44,50,60,64)

RoHS



PHYSICAL DATA

INSULATOR BODY : PBT, UL94V-0

CONTACT : COPPER ALLOY

ELECTRICAL DATA

RATED CURRENT : 3 AMPS

CONTACT RESISTANCE : 20m OHMS MAX

INSULATION RESISTANCE : 1000M OHMS MIN

DIELECTRIC WITHSTANDING : 1000V AC/DC

ENVIRONMENTAL DATA

TEMPERATURE RANGE : -40°C TO +105°C

PART NO: P9403IDS-XX-2XX-XX
XX = No.OF CONTACTS
(06-26,30,34,36,40,44,50,60,64)



6P	WITHOUT SLOT "M" AND "N"
8P-12P	WITH SLOT "M" AND WITHOUT SLOT "N"
14P-64P	WITH SLOT "M" AND "N"



Scale: NTS

Sht. Size: A4

Gen. Tol.: $\pm 0.35\text{mm}$
 $\pm 2^\circ$

ALL DIMENSIONS ARE IN MM.
IF UNLESS OTHERWISE SPECIFIED.



PROTECTRON[®]
ELECTROMECH (P) LTD

DESCRIPTION : IDC SOCKET 2.54mm PITCH DUAL ROW,
RoHS COMPLIANT

PART NO: P9403IDS-XX-2XX-XX
XX = No.OF CONTACTS
(06-26,30,34,36,40,44,50,60,64)

ORDERING INFORMATION

P9403IDS-XX-2XX-XX


NO.OF CONTACTS
06-64PINS

PLATING	
1	GOLD FLASH
4	TIN

-	WITH STRAIN
A	W/O STRAIN

BL	BLUE
GR	GREY
RE	RED
GN	GREEN
WH	WHITE
YE	YELLOW

Projection:



Scale: NTS

Sht. Size: A4

Gen. Tol.: $\pm 0.35\text{mm}$
 $\pm 2^\circ$

ALL DIMENSIONS ARE IN MM.
IF UNLESS OTHERWISE SPECIFIED.

www.protectron.in

protectron@protectron.in