


DESCRIPTION : 2.54x7.87mm PITCH FEMALE HEADER
SIDE ENTRY SINGLE ROW

PART NO: P9409-XX-21
XX = NO. OF CONTACTS



PHYSICAL DATA

INSULATION	
MATERIAL	: GLASS FILLED POLYESTER
FLAMMABILITY	: UL94V-0
COLOR	: BLACK
CONTACT	
MATERIAL	: COPPER ALLOY
FINISH	: GOLD PLATED
PACKAGING TYPE	: STANDARD PACKING

ELECTRICAL DATA

CURRENT RATING	: 3A
INSULATION RESISTANCE	: 1000M OHMS MIN
DIELECTRIC WITHSTANDING	: 1000V AC/MIN
CONTACT RESISTANCE	: 20m OHMS MAX

MECHANICAL DATA





INSERTION FORCE	: 200g max.
EXTRACTION FORCE	: 60g min.
MECHANICAL LIFE	: 200 CYCLES min.

ENVIRONMENTAL DATA

TEMPERATURE RANGE	: -55°C TO +105°C
-------------------	-------------------

DESCRIPTION : 2.54x7.87mm PITCH FEMALE HEADER
SIDE ENTRY SINGLE ROW

PART NO: P9409-XX-21
XX = NO. OF CONTACTS




ORDERING INFORMATION

P9409-XX-21

NO.OF CONTACTS
(02-40)

Projection:



Scale: NTS

Sht. Size: A4

Gen. Tol.: ±0.35mm

ALL DIMENSIONS ARE IN MM.
IF UNLESS OTHERWISE SPECIFIED.