




Female Headers

- ❑ Pitch:1.0mm/1.27mm/2.0mm/2.54mm
- ❑ Single row/Double row
- ❑ Straight/Right angle/SMT
- ❑ Machined contacts / Formed contacts

Pin Headers

- ❑ Pitch:1.0mm/1.27mm/2.0mm/2.54mm
- ❑ Single row/Double row
- ❑ Straight/Right angle/SMT



Pogo Pins

- ❑ Pogo Pins
- ❑ Threaded type pogo pins
- ❑ Operating Current :1 A



ABOUT US

Protectron Electromech is a manufacturer of professional grade circuit protection devices, interconnect solutions, EMI / RFI shielding products and cable assemblies. Our team has extensive experience across wide variety of industries and is focused on technology. Protectron customers include automotive, defense, telecom, computer, medical, lighting, domestic appliances and a host of other industrial users.

QUALITY ASSURANCE

With this focus over 30 years of industry experience, we strive to offer our customers high quality and value driven solutions. The assurance of quality and service is strengthened by the various product approvals and certifications. The company maintains a well documented system utilizing an ERP package for all manufacturing operations and quality assurance functions.

PRODUCT APPROVALS

Fuses- UL, RoHS, ARAI & LCSO
Connectors - RoHS, LCSO

CERTIFICATION

ISO 9001, 14001 & IATF 16949



PROTECTRON ELECTROMECH (P) LTD

#44, 29th Cross, 7th Main Road, Industrial Layout,
Banashankari II Stage, Bengaluru 560070
Karnataka, India

+91-80-4555 6005

protectron@protectron.in

www.protectron.in



making the perfect
Connection

**HIGH RELIABILITY
CONNECTORS**

2 Row Connectors

- ❑ Pitch:2.0 mm
- ❑ No of contacts: 4-60
- ❑ Male and female connectors
- ❑ Straight/Right angle/SMT
- ❑ Compliance MIL standards



Power & Signal Connector

- ❑ Power contact:15A
- ❑ Signal contact:2A
- ❑ No of poles:5
- ❑ IP rating : IP68




Circular Connector

- ❑ Voltage rating:600V
- ❑ Current rating:7.5A
- ❑ No of poles:6



3 Row Connectors

- ❑ Pitch:2.0 mm
- ❑ No of contacts: 11-206
- ❑ Male and female connectors
- ❑ Right angle
- ❑ Compliance MIL standards



Actuated Card Lock

- ❑ Lever actuated wedge action
- ❑ Spring actuated wedge action
- ❑ Defense application



Circuit Board Component Shielding

- ❑ Custom designed covers and fences
- ❑ Available in single part or two part construction



4 Row Connectors

- ❑ Pitch:2.0 mm
- ❑ No of contacts: 86-404
- ❑ Male and female connectors
- ❑ Right angle



Ethernet Connector

- ❑ Working Voltage : 100 V DC
- ❑ Current rating : 1.2A MAX at 25°C
- ❑ IP rating : IP67
- ❑ Panel mountable connector



D Sub Connector

- ❑ Working voltage : 60V
- ❑ Operating temperature range :-25°C to +105°C
- ❑ IP rating : IP67
- ❑ D sub plug waterproof

