## CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference 20150901-E228912 E228912-20150831

Issue Date

2015-SEPTEMBER-01

Issued to:

PROTECTRON ELECTROMECH (P) LTD

44 29TH CROSS 7TH MAIN ROAD BANASHANKARI INDUSTRIAL LAYOUT

BANASHANKARI II STAGE BANGALORE KA 560070 INDIA

This is to certify that representative samples of

COMPONENT - FUSES, SUPPLEMENTAL
Series PSF, PSFC, PST, PSTC, PMF and PMT.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 248-14 and CAN/CSA-C22.2 No. 248.14-00, Low-

Voltage Fuses - Part 14: Supplemental Fuses.

UL 248-1 and CSA C22.2 No. 248.1-11, Low-Voltage Fuses

- Part 1:General Requirements.

Additional Information:

'See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.

Bamely

Bruce Mahrenhoiz, Director North American Certification Program

ULLLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <a href="http://lyl.com/ai/outub/locations/">http://lyl.com/ai/outub/locations/</a>



File E228912 Vol. 1 Index

Page 2 Issued: 2002-11-10 New: 2015-08-31

| Type Designation   | Section | Report Date | Approvals |
|--|---------|-------------|-----------|
| Cat No. PSF 8A, PSF 10A,<br>PSFC 8A, PSFC 10A, PST 8A,<br>PST 10A, PSTC 8A, PSTC<br>10A.   |         | ė           |           |
| PMF followed by 0.63A, 0.8A, 1A, 1.25A, 1.6A, 2A, 2.5A, 3.15A, 4A, 5A, 6.3A.   | 4       | 2015-08-31  | В         |
| PMT followed by 0.1A,<br>0.125A, 0.16A, 0.2A, 0.25A,<br>0.315A, 0.4A, 0.5A, 0.63A,<br>0.8A, 1A, 1.25A, 1.6A, 2A,<br>2.5A, 3.15A, 4A, 5A, 6.3A. |         |             |           |

## Approvals Notes -

A - Evaluated to United States Standards only.
B - Evaluated to United States Standards and Canadian National Standards.
C - Evaluated to Canadian National Standards only.