

**8.5mm Subminiature Low breaking Capacity, Fast Blow Fuse-Round type**

Rated Current (A)	*Cooper Bussman	Littelfuse	Schurter	Protectron
0.05	-	3700050	0034.6000	<a href="#">PRFLT 0.05A</a>
0.063	-	3700063	0034.6001	<a href="#">PRFLT 0.063A</a>
0.08	-	3700080	0034.6002	<a href="#">PRFLT 0.08A</a>
0.1	-	3700100	0034.6003	<a href="#">PRFLT 0.1A</a>
0.125	-	3700125	0034.6004	<a href="#">PRFLT 0.125A</a>
0.16	-	3700160	0034.6005	<a href="#">PRFLT 0.16A</a>
0.2	-	3700200	0034.6006	<a href="#">PRFLT 0.2A</a>
0.25	-	3700250	0034.6007	<a href="#">PRFLT 0.25A</a>
0.315	-	3700315	0034.6008	<a href="#">PRFLT 0.315A</a>
0.4	-	3700400	0034.6009	<a href="#">PRFLT 0.4A</a>
0.5	-	3700500	0034.6010	<a href="#">PRFLT 0.5A</a>
0.63	-	3700630	0034.6011	<a href="#">PRFLT 0.63A</a>
0.8	SR-5F-800mA	3700800	0034.6012	<a href="#">PRFLT 0.8A</a>
1	SR-5F-1A	3701100	0034.6013	<a href="#">PRFLT 1A</a>
1.25	SR-5F-1.25A	3701125	0034.6014	<a href="#">PRFLT 1.25A</a>
1.6	SR-5F-1.6A	3701160	0034.6015	<a href="#">PRFLT 1.6A</a>
2	SR-5F-2A	3701200	0034.6016	<a href="#">PRFLT 2A</a>
2.5	SR-5F-2.5A	3701250	0034.6017	<a href="#">PRFLT 2.5A</a>
3.15	SR-5F-3.15A	3701315	0034.6018	<a href="#">PRFLT 3.15A</a>
4	SR-5F-4A	3701400	0034.6019	<a href="#">PRFLT 4A</a>
5	SR-5F-5A	3701500	0034.6020	<a href="#">PRFLT 5A</a>
6.3	SR-5F-6.3A	3701630	-	<a href="#">PRFLT 6.3A</a>

\* As Per UL Standard UL248-14

**8.5mm Subminiature Low breaking Capacity, Fast Blow Fuse-Rectangular type**

Rated Current (A)	*Cooper Bussman	*LittelFuse	Schurter	Protectron
0.05	-	3950050	-	<a href="#">PRFLT 0.05A-R</a>
0.063	-	3950063	-	<a href="#">PRFLT 0.063A-R</a>
0.08	-	3950080	-	<a href="#">PRFLT 0.08A-R</a>
0.1	-	3950100	-	<a href="#">PRFLT 0.1A-R</a>
0.125	-	3950125	-	<a href="#">PRFLT 0.125A-R</a>
0.16	-	3950160	7100.1057	<a href="#">PRFLT 0.16A-R</a>
0.2	-	3950200	7100.1058	<a href="#">PRFLT 0.2A-R</a>
0.25	-	3950250	7100.1059	<a href="#">PRFLT 0.25A-R</a>
0.315	-	3950315	7100.1060	<a href="#">PRFLT 0.315A-R</a>
0.4	-	3950400	7100.1061	<a href="#">PRFLT 0.4A-R</a>
0.5	-	3950500	7100.1062	<a href="#">PRFLT 0.5A-R</a>
0.63	-	3950630	7100.1063	<a href="#">PRFLT 0.63A-R</a>
0.8	SS-5F-800mA	3950800	7100.1064	<a href="#">PRFLT 0.8A-R</a>
1	SS-5F-1A	3951100	7100.1065	<a href="#">PRFLT 1A-R</a>
1.25	SS-5F-1.25A	3951125	7100.1066	<a href="#">PRFLT 1.25A-R</a>
1.6	SS-5F-1.6A	3951160	7100.1067	<a href="#">PRFLT 1.6A-R</a>
2	SS-5F-2A	3951200	7100.1068	<a href="#">PRFLT 2A-R</a>
2.5	SS-5F-2.5A	3951250	7100.1069	<a href="#">PRFLT 2.5A-R</a>
3.15	SS-5F-3.15A	3951315	7100.1070	<a href="#">PRFLT 3.15A-R</a>
4	SS-5F-4A	3951400	7100.1071	<a href="#">PRFLT 4A-R</a>
5	SS-5F-5A	3951500	7100.1072	<a href="#">PRFLT 5A-R</a>
6.3	SS-5F-6.3A	3951630	7100.1073	<a href="#">PRFLT 6.3A-R</a>

\* As Per UL Standard UL248-14

**Protectron Electromech Pvt Ltd, No.44, 29th Cross, 7th Main, BSK Indl. Layout,  
BSK 2nd stage, Bangalore-560 070, Tel.: +91 80 26716001-05  
email: [protectron@protectron.in](mailto:protectron@protectron.in)  
website: [www.protectron.in](http://www.protectron.in)**

**8.5mm Subminiature Low breaking Capacity, Slow Blow Fuse-Round type**

Rated Current (A)	Cooper Bussmann	Littelfuse	Schurter	Protectron
0.05	-	-	0034.6602	<a href="#">PRTL 0.05A</a>
0.063	-	-	0034.6603	<a href="#">PRTL 0.063A</a>
0.08	-	-	0034.6604	<a href="#">PRTL 0.08A</a>
0.1	SR-5-100mA	-	0034.6605	<a href="#">PRTL 0.1A</a>
0.125	SR-5-125mA	-	0034.6606	<a href="#">PRTL 0.125A</a>
0.16	SR-5-160mA	-	0034.6607	<a href="#">PRTL 0.16A</a>
0.2	SR-5-200mA	-	0034.6608	<a href="#">PRTL 0.2A</a>
0.25	SR-5-250mA	-	0034.6609	<a href="#">PRTL 0.25A</a>
0.315	SR-5-315mA	-	0034.6610	<a href="#">PRTL 0.315A</a>
0.4	SR-5-400mA	-	0034.6611	<a href="#">PRTL 0.4A</a>
0.5	SR-5-500mA	-	0034.6612	<a href="#">PRTL 0.5A</a>
0.63	SR-5-630mA	-	0034.6613	<a href="#">PRTL 0.63A</a>
0.8	SR-5-800mA	-	0034.6614	<a href="#">PRTL 0.8A</a>
1	SR-5-1A	3821100	0034.6615	<a href="#">PRTL 1A</a>
1.25	SR-5-1.25A	3821125	0034.6616	<a href="#">PRTL 1.25A</a>
1.6	SR-5-1.6A	3821160	0034.6617	<a href="#">PRTL 1.6A</a>
2	SR-5-2A	3821200	0034.6618	<a href="#">PRTL 2A</a>
2.5	SR-5-2.5A	3821250	0034.6619	<a href="#">PRTL 2.5A</a>
3.15	SR-5-3.15A	3821315	0034.6620	<a href="#">PRTL 3.15A</a>
4	SR-5-4A	3821400	0034.6621	<a href="#">PRTL 4A</a>
5	SR-5-5A	3821500	0034.6622	<a href="#">PRTL 5A</a>
6.3	SR-5-6.3A	3821630	0034.6623	<a href="#">PRTL 6.3A</a>

**8.5mm Subminiature Low breaking Capacity, Slow Blow Fuse-Rectangular type**

Rated Current (A)	Cooper Bussmann	Littelfuse	Protectron
0.25	-	-	<a href="#">PRTLTL 0.25A-R</a>
0.315	-	-	<a href="#">PRTLTL 0.315A-R</a>
0.4	SS-5-400mA	-	<a href="#">PRTLTL 0.4A-R</a>
0.5	SS-5-500mA	-	<a href="#">PRTLTL 0.5A-R</a>
0.63	SS-5-630mA	-	<a href="#">PRTLTL 0.63A-R</a>
0.8	SS-5-800mA	3920800	<a href="#">PRTLTL 0.8A-R</a>
1	SS-5-1A	3921100	<a href="#">PRTLTL 1A-R</a>
1.25	SS-5-1.25A	3921123	<a href="#">PRTLTL 1.25A-R</a>
1.6	SS-5-1.6A	3921160	<a href="#">PRTLTL 1.6A-R</a>
2	SS-5-2A	3921200	<a href="#">PRTLTL 2A-R</a>
2.5	SS-5-2.5A	3921250	<a href="#">PRTLTL 2.5A-R</a>
3.15	SS-5-3.15A	3921315	<a href="#">PRTLTL 3.15A-R</a>
4	SS-5-4A	3921400	<a href="#">PRTLTL 4A-R</a>
5	SS-5-5A	3921500	<a href="#">PRTLTL 5A-R</a>
6	SS-5-6.3A	3921630	<a href="#">PRTLTL 6.3A-R</a>